

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® Adhesive Agent

Revision date: 31.05.2022

Product code:

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

PLASTIFLOOR® Adhesive Agent

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture

Coatings.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	Plasti Chemie Produktionsgesellschaft mbH
Street:	Falgardring 1
Place:	D-08223 Falkenstein
Telephone:	+49(0)3745/74432-0 / +49(0)3745/74432-27
e-mail:	volkmar.lull@plasti-chemie.de
Contact person: Internet:	Mr.Volkmar Lull, +493745/74432-14

1.4. Emergency telephone number:

+49 (0)3745/74432-0
volkmar.lull@plasti-chemie.de Hr. Volkmar Lull
www.plasti-chemie.de volkmar.lull@plasti-chemie.de
Chemtrec: 1-800-424-9300 for US
+1 703-527-3887 outside US
NHS Direct (UK): +44 (0) 845 46 47; 111

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Classification according to regulation (EG) 1272/2008/WE

Flam. Liq. 2 H225, Skin Corr. 1 H314, Skin Sens. 1 H317, STOT SE 3 H335

Highly flammable liquid and vapour. Causes severe skin burns and eye damage. May cause allergic skin irritation.

May cause respiratory irritation.

2.2. Label elements GB

This substance is graded and classified according to (EG) Nr. 1272/2008 [2008]

Signal word: Danger**Pictograms:****Contains:** Methyl methacrylate, Methacryloyloxyethyl phosphate**Hazard statements**

H225	Heating may cause fire.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Precautionary statements

P210	Keep away from heat/sparks/open fire/hot surfaces and other ignition source. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® Adhesive Agent

Revision date: 31.05.2022

Product code:

Page 2 of 10

P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove person to fresh air and keep at rest in position comfortable for breathing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lens, if present and easy to do. Continue rinsing.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
80-62-6	Methylmethacrylat			10-50 %
	201-297-1	607-035-00-6	01-2119452498-28	
	Classification acc. to 1272/2008/WE: Flam. Liq. 2 H225, Skin Irrit. 2 H315, Skin Sens. 1 H317, STOT SE 3 H335			
52628-03-2	Methacryloyloxyethyl phosphate			50-100%
	258-053-2	.	.	
	Classification acc. to 1272/2008/WE: Skin Corr. 1 H314			

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

First aider: Pay attention to self-protection!

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth thoroughly with water. Let water be drunk in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Skin sensitization, corrosive effects, excessive or prolonged exposure may cause headaches or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® Adhesive Agent

Revision date: 31.05.2022

Product code:

Page 3 of 10

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Dry extinguishing powder. alcohol resistant foam.
In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Under certain fire conditions traces of other toxic substances are possible. Cracked Hydrocarbons, carbon monoxide and carbon dioxide.

5.3. Advice for firefighters

Airtight sealed containers may rupture explosively if heated.

Special protective equipment: Self-contained breathing apparatus, chemical-resistant protective clothing.

Additional information: Brand residues and contaminated firefighting water must be disposed according to the official regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition. Do not breathe vapours. Ensure adequate ventilation.

Use personal protective measures. Keep unprotected persons away.

Avoid skin and eye contamination.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Danger of explosion! Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Collect with non-flammable liquid absorbing material (e.g. sand, silica). Do not flush with water or aqueous cleaning agents. Collect in lockable and labelled containers. Treat the collected material as waste. Clean the contaminated place and ventilate it.

6.4. Reference to other sections

Disposal Section 13. Personal protective equipment Section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Follow general OSH regulations for dangerous chemical substances. Avoid contact with skin and eyes. Do not breathe vapours. Wash hands thoroughly before breaks and at the end of work. Use as intended. Keep container tightly closed. While handling the product do not eat, drink or smoke. No open flame or sparks. Keep the product away from heat and sources of ignition. Take measures to prevent electrostatic charging. Use non-sparking tools. Vapour can combine with air to form an explosive mixture. Avoid open flame, sparks, direct sunlight and other sources of ignition. Ensure good interior ventilation, especially at floor level (vapours are heavier than air and may pose a risk of explosion).

Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

The usual precautions for handling chemicals should be considered.

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® Adhesive Agent

Revision date: 31.05.2022

Product code:

Page 4 of 10

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing and wash it before reuse.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight. Ensure adequate ventilation of the storage area. Make sure spills can be contained (e.g. sump pallets or kerbed areas). Store in labelled and closed original container. Safely prevent any seepage into the ground. Store in well ventilated rooms. Store only outside or in explosion-proof rooms.

Hints on joint storage

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances. Store away from oxidizing agents (organic peroxides). Keep away from foodstuffs, beverages and food.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Protect against: UV-radiation/sunlight. heat. Humidity frost.

storage temperature: 5-25°C

Storage class: 3

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters Exposure limits (EH40)

DNEL/DMEL values

DNEL	Oral	Inhalation	Dermal
Worker, long-term, local effects	1	210 mg/m ³	1,5 mg/cm ²
Worker, long-term, systemic effects	1	210 mg/m ³	13,67 mg/kg KG/day
Worker, short-term, local effects	1	2	1,5 mg/cm ²
Worker, short-term, systemic effects	1	2	-
Consumers, long-term, local effects	1	105 mg/m ³	1,5 mg/cm ²
Consumers, long-term, systemic effects	1	74,3 mg/m ³	8,2 mg/kg KG/day
Consumers, short-term, local effects	1	2	1,5 mg/cm ²
Consumers, short-term, systemic effects	1	2	-

1) low oral toxicity: DNEL not calculated.

2) Long term DNEL

PNEC

80-62-06 Methyl methacrylate:

PNEC freshwater 0,94 mg/L

PNEC seawater 0,094 mg/L

PNEC sediment 5,74 mg/kg Dry weight

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® Adhesive Agent

Revision date: 31.05.2022

Product code:

Page 5 of 10

PNEC soil 1,47 mg/kg Dry weight

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Recommended eye protection brand: Tightly sealed safety glasses. (BS/EN 166)

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time \geq 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive EC/2016/425 and the standard EN 374 derived from it.

Skin protection

Wear fire/flammable resistant/retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Exceeding exposure limit values

Insufficient ventilation

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance:

Physical state: liquid

Colour: yellowish to brownish

Odour: characteristic

Odour threshold: Not determined.

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® Adhesive Agent

Revision date: 31.05.2022

Product code:

Page 6 of 10

Safety relevant basic data:

Parameters		Unit	Remark
Density:	1,21	g/cm ³	
Bulk density:			not determined
pH value:			not determined
Melting point/Melting range:	<0	°C	
Boiling point/Boiling range:	100	°C	
Flash point:	10	°C	MMA (DIN 51755)
Inflammability (solid/gaseous)			not determined
Explosion dangerousness:			
lower Explosion limit:			not determined
upper Explosion limit:			not determined
Ignition temperature			not determined
Vapour pressure			not determined
Viscosity	40-55	mPa.s	Brookfield

9.2. Other Information

No data

SECTION 10: Stability and reactivity**10.1. Reactivity**

The product is stable at intended storage and handling conditions.

10.2. Chemical stability

The product is stable at intended storage and handling conditions.

10.3. Possibility of hazardous reactions

In the presence of radical formers (e.g. peroxides), reducing substances and / or heavy metal ions exothermic polymerization is possible.

10.4. Conditions to avoid

Heat - , ignition sources, aging, contamination, oxygen-free atmosphere

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Strong acid.

10.6. Hazardous decomposition products

None at intended storage and handling conditions

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation**

Acute Toxicity:

Relevant LD/LC50 Values:

Oral	80-62-6 Methyl methacrylate:	LD50 (Rat) > 5000 mg/kg
	52628-03-2 Methacryloyloxyethyl phosphate:	LD50 (Rat) > 2000 mg/kg
Dermal	80-62-6 Methyl methacrylate:	LD50 (Rabbit) > 5000 mg/kg
Inhalation	80-62-6 Methyl methacrylate:	LC50 (Rat) > 29,8 mg/L / 4 h

Irritation to the skin: Corrosive .

Serious eye damage/irritation: Highly irritating and corrosive

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® Adhesive Agent

Revision date: 31.05.2022

Product code:

Page 7 of 10

Sensitization:	May cause allergic reactions.
Risk of aspiration toxicity:	Based on available data the classification criteria are not met.
CMR effects:	
Carcinogenicity	Based on available data the classification criteria are not met.
Germ cell mutagenicity	Based on available data the classification criteria are not met.
Reproductive toxicity	Based on available data the classification criteria are not met.
Other information:	
STOT – Single exposure	Based on available data the classification criteria are not met.
STOT – Repeated exposure	Based on available data the classification criteria are not met.

11.2. Information on other hazards Endocrine disrupting properties

No data available.

SECTION 12: Ecological information**12.1. Toxicity**

Aquatic Toxicity

Product	LC 50 (Poecilia reticulata):	>100 mg/L / 96 h (OECD 203)
	EC 50 (daphnia magna):	>100 mg/L / 48 h (OECD 202)
Methyl methacrylate	EC 3 (salineastrum capricornutum):	> 110 mg/L / 72 h (OECD 201)
	EC 0 (pseudomonas putida):	100mg/L / 16 h

12.2. Persistence and degradability

Product is easily biodegradable according to OECD criteria. In the air the substance is rapidly degraded photo chemically.

Main component of the mixture: Methyl methacrylate is easily biodegradable.

12.3. Bioaccumulative potential

Due to the distribution coefficient n-octanol-water (log Pow) accumulation in organisms is not expected.

12.4. Results of PBT and vPvB assessment

A binding to the solid phase soil, sediment or sludge is not expected. The substance slowly evaporates from the water surface into the atmosphere. If the substance gets into the environment it remains preferably in the compartment to which it has emerged.

12.5. Mobility in soil

No further information relevant

12.6. Other adverse effects

No further information relevant

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES, PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® Adhesive Agent

Revision date: 31.05.2022

Product code:

Page 8 of 10

List of Wastes Code - used product

080299

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

List of Wastes Code - contaminated packaging

150110

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:**

UN 2924

14.2. UN proper shipping name:

ADR 2924 Flammable Liquid, Corrosive, N.O.S. (contains methyl methacrylate, phosphoric acid esters)

IMDG, IATA Flammable Liquid, Corrosive, N.O.S. (contains methyl methacrylate, phosphoric acid esters)

14.3. Transport hazard class(es):

ADR



Class: 3 (F1) flammable liquids, 8 Corrosive

IMDG, IATA



Class: 3 (F1) flammable liquids, 8 Corrosive

14.4. Packing group

II

14.5. Environmental hazards

Marine pollutant: No

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**Not applicable**

Transport/Additional information:

ADR:

Limited quantities (LQ): 5 L

Transport category: 3

Tunnel restriction code: D/E

RID/GGVCEB see ADR

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® Adhesive Agent

Revision date: 31.05.2022

Product code:

Page 9 of 10

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

National regulations

This product has to be labelled in accordance with the Ordinance on Hazardous Substances in the latest version.

Employment restrictions

Observe employment restrictions for young people.

Observe employment restrictions for expectant and nursing mothers.

Other regulations, limitations and prohibitive regulations

Note:

Apply the appropriate local regulations.

15.2. Chemical safety assessment

A chemical safety assessment is not required for this product.

SECTION 16: Other information**Changes**

Rev. 1.00; Initial release: 25.05.2021

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service CLP: Classification, Labelling and Packaging of substances and mixtures DNEL: Derived No Effect Level

d: day(s)

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

ECHA: European Chemicals Agency

EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect concentration

NLP: No-Longer Polymers

N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration

PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® Adhesive Agent

Revision date: 31.05.2022

Product code:

Page 10 of 10

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern

TRGS: Technische Regeln für Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)