

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Plastifloor® 800 PUMMA -Harz

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coatings.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	Plasti Chemie Produktionsgesellschaft mbH	
Street:	Falgardring 1	
Place:	D-08223 Falkenstein	
Telephone:	+49 (0)3745/74432-0	Telefax: +49 (0)3745/74432-27
e-mail:	volkmar.lull@plasti-chemie.de	
Contact person:	Hr. Volkmar Lull	Telephone: +49 (0)3745/74432-0
Internet:	www.plasti-chemie.de	
Responsible Department:	volkmar.lull@plasti-chemie.de	

1.4. Emergency telephone

number: Chemtrec: 1-800-424-9300 for US
+1 703-527-3887 outside US
NHS Direct (UK): +44 (0) 845 46 47; 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:
Flammable liquid: Flam. Liq. 2
Skin corrosion/irritation: Skin Irrit. 2
Respiratory or skin sensitisation: Skin Sens. 1
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Chronic 3
Hazard Statements:
Highly flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.
Harmful to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate
2-ethylhexyl acrylate
n-butyl methacrylate
Tetramethylene dimethacrylate
2,2-bis[[(mercaptoacetyl)oxy]methyl]-1,3-propanediyl bis(mercaptoacetate)

Signal word: Danger

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 2 of 16

Pictograms:

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.
 The substances in the mixture (>0,1%) do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures
Hazardous components

CAS No	Chemical name	Quantity
	EC No Index No REACH No	
	GHS Classification	
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	50 - 100 %
	201-297-1 607-035-00-6 01-2119452498-28	
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335	
103-11-7	2-ethylhexyl acrylate	25 - < 30 %
	203-080-7 607-107-00-7 01-2119453158-37	
	Skin Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 3; H315 H317 H335 H412	
97-88-1	n-butyl methacrylate	5 - < 7 %
	202-615-1 607-033-00-5 01-2119486394-28	
	Flam. Liq. 3, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H226 H315 H319 H317 H335	
2082-81-7	Tetramethylene dimethacrylate	0.5 - < 1 %
	218-218-1 01-2119967415-30	
	Skin Sens. 1B; H317	
38668-48-3	1,1'-(p-tolylimino)dipropan-2-ol	0.5 - < 1 %
	254-075-1	
	Acute Tox. 2, Eye Irrit. 2, Aquatic Chronic 3; H300 H319 H412	
10193-99-4	2,2-bis[[(mercaptoacetyl)oxy]methyl]-1,3-propanediyl bis(mercaptoacetate)	0.2 - < 0.3 %
	233-482-8	
	Acute Tox. 4, Skin Sens. 1A; H302 H317	

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 3 of 16

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
80-62-6	201-297-1	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	50 - 100 %
		inhalation: LC50 = 29,8 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = >5000 mg/kg	
103-11-7	203-080-7	2-ethylhexyl acrylate	25 - < 30 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 4435 mg/kg	
97-88-1	202-615-1	n-butyl methacrylate	5 - < 7 %
		inhalation: LC50 = 29 mg/l (dusts or mists); dermal: LD50 = 10181 mg/kg; oral: LD50 = > 17900 mg/kg	
2082-81-7	218-218-1	Tetramethylene dimethacrylate	0.5 - < 1 %
		dermal: LD50 = > 3000 mg/kg; oral: LD50 = (10,066) mg/kg	
38668-48-3	254-075-1	1,1'-(p-tolylimino)dipropan-2-ol	0.5 - < 1 %
		oral: LD50 = 25 - 200 mg/kg	
10193-99-4	233-482-8	2,2-bis[[[(mercaptoacetyl)oxy]methyl]-1,3-propanediyl bis(mercaptoacetate)	0.2 - < 0.3 %
		oral: ATE = 500 mg/kg	

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

First aider: Pay attention to self-protection!

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 4 of 16

Suitable extinguishing media

Carbon dioxide (CO₂). Dry extinguishing powder. alcohol resistant foam.
In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Remove persons to safety. Remove all sources of ignition. Ventilate affected area.
Wear personal protection equipment. (See section 8.)

For emergency responders

No special measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Danger of explosion! Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations.

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 5 of 16

Advice on general occupational hygiene

The usual precautions for handling chemicals should be considered.

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing and wash it before reuse.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.

Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases.

Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Protect against: UV-radiation/sunlight. heat. Humidity frost.

storage temperature: 5-25°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
68-11-1	Mercaptoacetic acid	1	3.8		TWA (8 h)	WEL
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate			
Worker DNEL, acute		inhalation	local	416 mg/m ³
Consumer DNEL, acute		inhalation	local	208 mg/m ³
Consumer DNEL, long-term		oral	systemic	8,2 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	348,4 mg/m ³
Worker DNEL, long-term		dermal	systemic	13,67 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,5 mg/cm ²
Worker DNEL, acute		dermal	local	1,5 mg/cm ²

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 6 of 16

Worker DNEL, long-term	inhalation	local	208 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	74,3 mg/m ³
Consumer DNEL, long-term	inhalation	local	104 mg/m ³
Consumer DNEL, long-term	dermal	systemic	8,2 mg/kg bw/day
Consumer DNEL, long-term	dermal	local	1,5 mg/cm ²
Consumer DNEL, acute	dermal	local	1,5 mg/cm ²
97-88-1	n-butyl methacrylate		
Worker DNEL, long-term	dermal	local	1 %
Worker DNEL, acute	dermal	local	1 %
Consumer DNEL, long-term	dermal	local	1 %
Consumer DNEL, acute	dermal	local	1 %
Consumer DNEL, long-term	inhalation	systemic	66,5 mg/m ³
Consumer DNEL, long-term	dermal	systemic	3 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	366,4 mg/m ³
Worker DNEL, long-term	inhalation	local	409 mg/m ³
Worker DNEL, long-term	dermal	systemic	5 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	415,9 mg/m ³
2082-81-7	Tetramethylene dimethacrylate		
Worker DNEL, long-term	inhalation	systemic	14,5 mg/m ³
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	4,3 mg/m ³
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day
128-37-0	2,6-di-tert-butyl-p-cresol		
Worker DNEL, long-term	inhalation	systemic	3,5 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,86 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day
68-11-1	thioglycolic acid		
Worker DNEL, long-term	inhalation	systemic	1,58 mg/m ³
Worker DNEL, acute	inhalation	systemic	4,54 mg/m ³
Worker DNEL, acute	inhalation	local	4,54 mg/m ³
Worker DNEL, long-term	dermal	systemic	2,24 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,28 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,8 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,08 mg/kg bw/day

PNEC values

CAS No	Substance	Value
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 7 of 16

Freshwater	0,94 mg/l
Freshwater (intermittent releases)	0,94 mg/l
Marine water	0,094 mg/l
Freshwater sediment	10,2 mg/kg
Marine sediment	0,102 mg/kg
Micro-organisms in sewage treatment plants (STP)	10 mg/l
Soil	1,48 mg/kg
97-88-1	n-butyl methacrylate
Freshwater	0,017 mg/l
Freshwater (intermittent releases)	0,056 mg/l
Marine water	0,002 mg/l
Freshwater sediment	4,73 mg/kg
Marine sediment	0,473 mg/kg
Micro-organisms in sewage treatment plants (STP)	31,7 mg/l
Soil	0,935 mg/kg
2082-81-7	Tetramethylene dimethacrylate
Freshwater	0,043 mg/l
Freshwater (intermittent releases)	0,098 mg/l
Marine water	0,004 mg/l
Freshwater sediment	3,12 mg/kg
Marine sediment	0,312 mg/kg
Micro-organisms in sewage treatment plants (STP)	2 mg/l
Soil	0,573 mg/kg
128-37-0	2,6-di-tert-butyl-p-cresol
Freshwater	0,000199 mg/l
Freshwater (intermittent releases)	0,00199 mg/l
Marine water	0,00002 mg/l
Freshwater sediment	0,0996 mg/kg
Marine sediment	0,00996 mg/kg
Secondary poisoning	8,33 mg/kg
Micro-organisms in sewage treatment plants (STP)	0,17 mg/l
Soil	0,04769 mg/kg
68-11-1	thioglycolic acid
Freshwater	0,027 mg/l
Freshwater (intermittent releases)	0,27 mg/l
Marine water	0,003 mg/l
Freshwater sediment	0,1 mg/kg
Marine sediment	0,01 mg/kg
Micro-organisms in sewage treatment plants (STP)	0,5 mg/l
Soil	0,004 mg/kg

8.2. Exposure controls

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 8 of 16



Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Recommended eye protection brand: Tightly sealed safety glasses. (BS/EN 166)

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time \geq 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive EC/2016/425 and the standard EN 374 derived from it.

Skin protection

Wear fire/flame resistant/retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Exceeding exposure limit values

Insufficient ventilation

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	white, cloudy
Odour:	characteristic

Test method

Changes in the physical state

Melting point/freezing point: not applicable

Boiling point or initial boiling point and boiling range: not determined

Flash point: 10 (MMA) °C DIN 51755

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 9 of 16

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:	2,1 (MMA) vol. %
Upper explosion limits:	12,5 (MMA) vol. %
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / dynamic: (at 40 °C)	not determined
Viscosity / kinematic: (at 20 °C)	not determined
Flow time:	not determined
Water solubility:	insoluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:	SECTION 12: Ecological information
Vapour pressure: (at 20 °C)	38,7 (MMA) hPa
Density:	not determined
Relative vapour density:	not determined

9.2. Other information**Information with regard to physical hazard classes**Oxidizing properties
none.**Other safety characteristics**

Solvent separation test:	not determined
Solvent content:	not determined
Solid content:	not determined
Evaporation rate:	not determined

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactionsReacts with : Amines
Refer to chapter 10.5.**10.4. Conditions to avoid**Keep away from heat. Danger of explosion!
In use may form flammable/explosive vapour-air mixture.
Heating causes rise in pressure with risk of bursting.

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 10 of 16

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Strong acid.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicokinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	WoE
	dermal	LD50 > 5000 mg/kg	Rabbit	ECHA Dossier	OECD Guideline 402
	inhalation (4 h) aerosol	LC50 29,8 mg/l	Rat	ECHA Dossier	
103-11-7	2-ethylhexyl acrylate				
	oral	LD50 4435 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
97-88-1	n-butyl methacrylate				
	oral	LD50 > 17900 mg/kg	Rat	J. Ind. Hyg. Toxicol. 23: 343-351 (1941)	other: pre-guideline development
	dermal	LD50 10181 mg/kg	Rabbit	Amer. Ind. Hyg. Assoc. J. Vol 30 (5): 47	other
	inhalation (4 h) aerosol	LC50 29 mg/l	Rat	ECHA Dossier	
2082-81-7	Tetramethylene dimethacrylate				
	oral	LD50 (10,066) mg/kg	Rat	Study report (1978)	OECD Guideline 401
	dermal	LD50 > 3000 mg/kg	Rabbit	Kirk-Othmer, Encyclopedia of chemical te	
38668-48-3	1,1'-(p-tolylimino)dipropan-2-ol				
	oral	LD50 25 - 200 mg/kg	Rat.	Lanxess	
10193-99-4	2,2-bis[[(mercaptoacetyl)oxy]methyl]-1,3-propanediyl bis(mercaptoacetate)				
	oral	ATE 500 mg/kg			

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 11 of 16

May cause an allergic skin reaction. (methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; 2-ethylhexyl acrylate; n-butyl methacrylate; Tetramethylene dimethacrylate; 2,2-bis[[[mercaptoacetyl]oxy]methyl]-1,3-propanediyl bis(mercaptoacetate))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; 2-ethylhexyl acrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available.

11.2. Information on other hazards
Endocrine disrupting properties

No data available.

SECTION 12: Ecological information
12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate					
	Acute fish toxicity	LC50 >79 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier	EPA OTS 797.1400
	Acute algae toxicity	ErC50 mg/l >110	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 69 mg/l	48 h	Daphnia magna	ECHA Dossier	EPA OTS 797.1300
	Fish toxicity	NOEC 9,4 mg/l	35 d	Brachydanio rerio	ECHA Dossier	
	Crustacea toxicity	NOEC 37 mg/l	21 d	Daphnia magna	ECHA Dossier	OECD Guideline 211
	Acute bacteria toxicity	(100 mg/l)		activated sludge	ECHA Dossier	OECD 301C
103-11-7	2-ethylhexyl acrylate					
	Acute fish toxicity	LC50 1,81 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier	
	Acute algae toxicity	ErC50 1,71 mg/l	72 h	Desmodesmus subspicatus	ECHA Dossier	
	Acute crustacea toxicity	EC50 1,3 mg/l	48 h	Daphnia magna	ECHA Dossier	
97-88-1	n-butyl methacrylate					
	Acute fish toxicity	LC50 11 mg/l	96 h	Pimephales promelas	Study report (1993)	OECD Guideline 203
	Acute algae toxicity	ErC50 31,2 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50 25,4 mg/l	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Crustacea toxicity	NOEC 1,1 mg/l	21 d	Daphnia magna	Study report (1998)	OECD Guideline 211
2082-81-7	Tetramethylene dimethacrylate					

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 12 of 16

	Acute algae toxicity	ErC50 mg/l	(4,97)	72 h	Desmodesmus subspicatus	REACH Dossier	OECD Guideline 201
	Crustacea toxicity	NOEC mg/l	5,09	21 d	Daphnia magna	REACH Dossier	OECD Guideline 211

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate			
	OECD 301C / ISO 9408 / EWG 92/69 Anhang V, C.4-F	94%	14	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			
103-11-7	2-ethylhexyl acrylate			
	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D	>80%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			
97-88-1	n-butyl methacrylate			
	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	88%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential
Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	1,32
103-11-7	2-ethylhexyl acrylate	4,64 (25°C)
97-88-1	n-butyl methacrylate	2,99
2082-81-7	Tetramethylene dimethacrylate	3,1

BCF

CAS No	Chemical name	BCF	Species	Source
97-88-1	n-butyl methacrylate	70		J. Fish Board Can. 3

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture (>0,1%) do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 13 of 16

List of Wastes Code - residues/unused products

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

List of Wastes Code - used product

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: RESIN SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: Resin solution
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2

Marine transport (IMDG)

Safety Data Sheet

according to UK REACH Regulation

Revision date: 23.05.2022	Plastifloor® 800 PUMMA -Harz	Product code:
		Page 14 of 16

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: RESIN SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Marine pollutant: NO
 Special Provisions: -
 Limited quantity: 5 L
 Excepted quantity: E2
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: RESIN SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2010/75/EU (VOC): not determined

2004/42/EC (VOC): not determined

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 15 of 16

Safety Data Sheet according to UK-REACH Regulation

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

UK REACH Appendix XVII, No (mixture): 3, 40

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

2-ethylhexyl acrylate

Tetramethylene dimethacrylate

SECTION 16: Other information

Changes

Rev. 1.00; Initial release: 10.12.2021

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

ECHA: European Chemicals Agency

EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect concentration

NLP: No-Longer Polymers

N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration

PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern

TRGS: Technische Regeln für Gefahrstoffe

UN: United Nations

Safety Data Sheet

according to UK REACH Regulation

Plastifloor® 800 PUMMA -Harz

Revision date: 23.05.2022

Product code:

Page 16 of 16

VOC: Volatile Organic Compounds

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H300	Fatal if swallowed.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)