

**Safety Data Sheet**

according to UK REACH Regulation

**PLASTIFLOOR® 050**

Revision date: 01.06.2022

Product code:

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

PLASTIFLOOR® 050

**1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture**

Coatings.

**Uses advised against**

Any non-intended use.

**1.3. Details of the supplier of the safety data sheet**

Company name:	Plasti Chemie Produktionsgesellschaft mbH
Street:	Falgardring 1
Place:	D-08223 Falkenstein
Telephone:	+49(0)3745/74432-0 / +49(0)3745/74432-27
e-mail:	volkmar.lull@plasti-chemie.de
Contact person: Internet:	Mr.Volkmar Lull, +493745/74432-14

**1.4. Emergency telephone number:**

+49 (0)3745/74432-0  
volkmar.lull@plasti-chemie.de Hr. Volkmar Lull  
www.plasti-chemie.de volkmar.lull@plasti-chemie.de  
Chemtrec: 1-800-424-9300 for US  
+1 703-527-3887 outside US  
NHS Direct (UK): +44 (0) 845 46 47; 111

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Classification according to regulation (EG) 1272/2008/WE

Flam. Liq. 2 H225, Skin Irrit. 2 H315, Skin Sens. 1 H317, Eye Irrit. 2 H319, STOT SE 3 H335

Highly flammable liquid and vapour. Causes skin irritation. May cause allergic skin reaction. Causes serious eye irritation.

May cause respiratory irritation.

**2.2. Label elements GB**

This substance is graded and classified according to (EG) Nr. 1272/2008 [2008]

**Signal word:** Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
------	--

## Safety Data Sheet

according to UK REACH Regulation

### PLASTIFLOOR® 050

Revision date: 01.06.2022

Product code:

Page 2 of 10

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove person to fresh air and keep at rest in position comfortable for breathing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lens, if present and easy to do. Continue rinsing.

#### 2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
3077-12-1	N,N-Di-(2-hydroxyethyl)-p-toluidine			< 1 %
	221-359-1			
	Classification acc. to 1272/2008/WE: Acute Tox. 4 H302, Eye Dam 1 H318			
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy			<1%
	265-185-4	649-330-00-2	-	
	Classification acc. to 1272/2008/WE: Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411			

##### Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

First aider: Pay attention to self-protection!

##### After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

##### After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

##### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

##### After ingestion

Rinse mouth thoroughly with water. Let water be drunk in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated skin contact may cause irritation, reddening, dry skin, allergic skin irritation, itching, rash. After eye

## Safety Data Sheet

according to UK REACH Regulation

### PLASTIFLOOR® 050

Revision date: 01.06.2022

Product code:

Page 3 of 10

contact reddening, watery eyes, burning eyes, irritation may occur. Swallowing may cause stomach pain, nausea, vomiting. High vapour concentration may cause headache, dizziness and respiratory irritation.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

No further information relevant

### SECTION 5: Firefighting measures

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>). Dry extinguishing powder. alcohol resistant foam.  
In case of major fire and large quantities: Atomized water.

##### **Unsuitable extinguishing media**

High power water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Under certain fire conditions traces of other toxic substances are possible. Cracked Hydrocarbons, carbon monoxide and carbon dioxide.

#### **5.3. Advice for firefighters**

Highly flammable liquid and vapour. Heat can cause polymerization. Airtight sealed containers may rupture explosively if heated.

Special protective equipment: Self-contained breathing apparatus, chemical-resistant protective clothing.

Additional information: Brand residues and contaminated firefighting water must be disposed according to the official regulations.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Exclude sources of ignition.

Do not breathe vapours. Ensure adequate ventilation.

Use personal protective measures. Keep unprotected persons away.

Avoid skin and eye contamination.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Danger of explosion! Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### **6.3. Methods and material for containment and cleaning up**

Collect with non-flammable liquid absorbing material (e.g. sand, silica). Do not flush with water or aqueous cleaning agents. Collect in lockable and labelled containers. Treat the collected material as waste. Clean the contaminated place and ventilate it.

#### **6.4. Reference to other sections**

Disposal Section 13. Personal protective equipment Section 8

### SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**

Follow general OSH regulations for dangerous chemical substances. Avoid contact with skin and eyes. Do not breathe vapours. Wash hands thoroughly before breaks and at the end of work. Use as intended. Keep container tightly closed. While handling the product do not eat, drink or smoke. No open flame or sparks. Keep the product away from heat and sources of ignition. Take measures to prevent electrostatic charging. Use non-sparking tools. Vapour can combine with air to form an explosive mixture. Avoid open flame, sparks, direct sunlight and other sources of ignition. Ensure good interior ventilation, especially at floor level (vapours are heavier than air and may pose a risk of explosion).

## Safety Data Sheet

according to UK REACH Regulation

### PLASTIFLOOR® 050

Revision date: 01.06.2022

Product code:

Page 4 of 10

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

- Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.
- Ensure adequate ventilation of the storage area.
- Make sure spills can be contained (e.g. sump pallets or kerbed areas).

##### Hints on joint storage

- Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

##### Further information on storage conditions

- Keep the packing dry and well sealed to prevent contamination and absorption of humidity.
- Protect against: UV-radiation/sunlight. heat. Humidity frost.
- storage temperature: 5-25°C
- storage class: 3

#### 7.3. Specific end use(s)

See section 1.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters Exposure limits (EH40)

##### DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
80-62-6	Methyl methacrylate		
Worker DNEL, long-term	inhalation	systemic	208 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	13.67 mg/kg bw/day
Worker DNEL, long-term	dermal	local	1.5 mg/cm <sup>2</sup>
Worker DNEL, acute	dermal	local	1.5 mg/cm <sup>2</sup>
Worker DNEL, long-term	inhalation	local	208 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	systemic	74.3 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local	104 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	8.2 mg/kg bw/day
Consumer DNEL, long-term	dermal	local	1.5 mg/cm <sup>2</sup>
Consumer DNEL, acute	dermal	local	1.5 mg/cm <sup>2</sup>

##### PNEC values

CAS No	Substance	
Environmental compartment	Value	
80-62-6	Methyl methacrylate	
Freshwater	0.94 mg/l	
Marine water	0.94 mg/l	
Freshwater sediment	5.74 mg/kg	
Micro-organisms in sewage treatment plants (STP)	10 mg/l	
Soil	1.47 mg/kg	

#### 8.2. Exposure controls

**Safety Data Sheet**

according to UK REACH Regulation

**PLASTIFLOOR® 050**

Revision date: 01.06.2022

Product code:

Page 5 of 10



**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaustion at critical locations.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Recommended eye protection brand: Tightly sealed safety glasses. (BS/EN 166)

**Hand protection**

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time  $\geq$  480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive EC/2016/425 and the standard EN 374 derived from it.

**Skin protection**

Wear fire/flame resistant/retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

**Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Exceeding exposure limit values

Insufficient ventilation

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

**Environmental exposure controls**

Do not allow uncontrolled discharge of product into the environment.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Appearance:

Physical state: liquid

Colour: White

Odour: Characteristic

Odour threshold: Not determined.

Safety relevant basic data:

Parameters	Unit	Remark
Density:	1	g/cm <sup>3</sup>
Bulk density:		not determined

**Safety Data Sheet**

according to UK REACH Regulation

**PLASTIFLOOR® 050**

Revision date: 01.06.2022

Product code:

Page 6 of 10

pH value:

Melting point/Melting range:

not determined

Boiling point/Boiling range:

100 °C

MMA

Flash point:

10 °C

MMA (DIN 51755)

Inflammability (solid/gaseous)

not determined

Explosion dangerousness:

lower Explosion limit:

2,1 Vol%

(MMA)

upper Explosion limit:

12,5 Vol%

(MMA)

Ignition temperature

430 °C

Vapour pressure

38,7 hPa

at20°C (MMA)

Viscosity

20-40 mPa.s

Brookfield

**9.2. Other Information**

VOC: 0,01%

**SECTION 10: Stability and reactivity**
**10.1. Reactivity**

Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators.

**10.2. Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature.

**10.3. Possibility of hazardous reactions**

Reacts with : Amines

Refer to chapter 10.5.

**10.4. Conditions to avoid**

Keep away from heat. Danger of explosion!

In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting.

**10.5. Incompatible materials**

Materials to avoid: Oxidizing agents, strong. Strong acid.

**10.6. Hazardous decomposition products**

Does not decompose when used for intended uses.

 Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO<sub>2</sub>).

**SECTION 11: Toxicological information**
**11.1. Information on hazard classes as defined in GB CLP Regulation**
**Toxicokinetics, metabolism and distribution**

	LD 50 Oral	LD50 Dermal	LC50 Inhalation
Methylmethacrylat	>5000 mg/kg (Rat)	>5000 mg/kg (rabbit)	29,8 mg/L (Rat) 4h
N,N-Di-(2-hydroxyethyl)-p-toluidine	>100 mg/kg (Rat)		

Causes skin irritation.

Causes serious eye irritation.

May cause allergic reactions.

**11.2. Information on other hazards Endocrine disrupting properties**

No data available.

**SECTION 12: Ecological information**

## Safety Data Sheet

according to UK REACH Regulation

### PLASTIFLOOR® 050

Revision date: 01.06.2022

Product code:

Page 7 of 10

#### 12.1. Toxicity

##### Aquatic Toxicity

Methylmethacrylat	EC 50 (daphnia magna): 69 mg/L / 48 h (OECD 202) NOEC (daphnia magna): 37mg/L (OECD 202 Part 2, 21d) EC 50 (salneastrum capricornutum): > 110 mg/L / 72 h (OECD 201) EC 3 (pseudomonas putida): 100mg/L / 16 h LC 50 (oncorhynchus mykiss): > 79 mg/L / 96 h NOEC (danio rerio): >9,4 mg/L (OECD 210) BSB5: 0,14 g O2/g
N,N-Di-(2-hydroxyethyl)-p-toluidine:	EC 50 (daphnia magna): 28,8 mg/L LC 50 (danio rerio): 17 mg/L BSB5 11 mg O2/g: CSB: 2360 mg O2/g

#### 12.2. Persistence and degradability

Main component of the mixture: Methyl methacrylate is easily biodegradable

#### 12.3. Bioaccumulative potential

Low bioaccumulative potential.

#### 12.4. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.5. Mobility in soil

The product is mobile in soils.

#### 12.6. Other adverse effects

Water hazard class 2 (self-classification): hazardous for water.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

#### **List of Wastes Code - residues/unused products**

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

#### **List of Wastes Code - used product**

080299

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

#### **List of Wastes Code - contaminated packaging**

150110

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging

**Safety Data Sheet**

according to UK REACH Regulation

**PLASTIFLOOR® 050**

Revision date: 01.06.2022

Product code:

Page 8 of 10

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)****14.1. UN number:** UN 1866**14.2. UN proper shipping name:**

ADR Class: 3 (F1) flammable liquids



IMDG, IATA Class: 3 (F1) flammable liquids

**14.3. Transport hazard class(es):**

ADR 1866 Resin Solution

IMDG, IATA Resin Solution

**14.4. Packing group** II**14.5. Environmental hazards**

Marine pollutant: No

**14.6. Special precautions for user**

Kemler-number: 33

EMS-Number: F-S, S-E

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

Transport/Additional information: ADR

Limited quantities (LQ) 5l

Transport category: 2

Tunnel restriction code: D/E

RID/GGVCEB see ADR

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC):

2004/42/EC (VOC):

Information according to 2012/18/EU (SEVESO III):

**Additional information**

not determined

not determined

P5c FLAMMABLE LIQUIDS



**Safety Data Sheet**

according to UK REACH Regulation

**PLASTIFLOOR® 050**

Revision date: 01.06.2022

Product code:

Page 9 of 10

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)  
The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].  
REACH 1907/2006 Appendix XVII, No (mixture): 3, 40

**National regulatory information**

Employment restrictions:

Water hazard class (D):

**15.2. Chemical safety assessment**

A chemical safety assessment is not required for this product.

**SECTION 16: Other information****Changes**

Rev. 1.00; Initial release: 25.05.2021

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
CAS: Chemical Abstracts Service  
CLP: Classification, Labelling and Packaging of substances and mixtures  
DNEL: Derived No Effect Level  
d: day(s)  
EINECS: European INventory of Existing Commercial chemical Substances  
ELINCS: European List of Notified Chemical Substances  
ECHA: European Chemicals Agency  
EWC: European Waste Catalogue  
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
h: hour  
LOAEL: Lowest observed adverse effect level  
LOAEC: Lowest observed adverse effect concentration  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
NOAEL: No observed adverse effect level  
NOAEC: No observed adverse effect concentration  
NLP: No-Longer Polymers  
N/A: not applicable  
OECD: Organisation for Economic Co-operation and Development  
PNEC: predicted no effect concentration  
PBT: Persistent bioaccumulative toxic  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )  
REACH: Registration, Evaluation, Authorisation of Chemicals  
SVHC: substance of very high concern  
TRGS: Technische Regeln für Gefahrstoffe  
UN: United Nations  
VOC: Volatile Organic Compounds

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data

**Safety Data Sheet**

according to UK REACH Regulation

**PLASTIFLOOR® 050**

Revision date: 01.06.2022

Product code:

Page 10 of 10

Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Further Information**

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*